

<b>DRS-45 SPECS</b>	
Power Requirements Weight Dimensions(WxHxD) Power Consumption Tape Speed Video System Colour LCD monitor	AC 100-240 V, 50/60 Hz 4.6 kg 212 x 98 x 392.8 mm 22W Approx. 28.2 mm/sec.(DVCAM 625/50 (PAL) 2-inch type, 123,200 dots
<b>Video Input</b>	
Composite Component S-Video	BNC x1, 1.0 Vp-p, 75 ohm. Sync BNC x3, Y: 1.0 Vp-p, 75 ohm, Sync DIN 4-pin x1, Y: 1.0 Vp-p, 75 ohm,
<b>Video Output</b>	
Composite Component S-Video Audio Input	BNC x1, 1.0 Vp-p, 75 ohm. Sync BNC x3, Y: 1.0 Vp-p, 75 ohm, Sync DIN 4-pin x1, Y: 1.0 Vp-p, 75 ohm, Phono jacks (x4), -10/-2/+4 dBu
<b>Audio Output</b>	
Line Monitor Headphone Digital IN/OUT RS-232C RS-422A LANC Control S	XLR 3-pin male (x4), +4 dBu Phono jack (x1), monaural Stereo mini headphone jack (x1) DV IN/OUT, IEEE1394 based, 4 pin D-sub 9-pin x1, male D-sub 9-pin x1, female Stereo mini jack x1 Stereo mini jack IN x1